


polkaudio[®]

the speaker specialists[®]

700-LS & 70-RT

Mounting Template and Instructions Gabarit D'Installation et Consignes

Follow these steps while installing the 700-LS & 70-RT
Étapes à suivre pour installer 700-LS & 70-RT

- 
- | | |
|--|---|
| <ol style="list-style-type: none">1) Determine speaker location. Be sure that it does not interfere with studs/joists.2) Hold or tape the template to the mounting location.3) Trace along the outside of the template.4) Carefully cut a hole ensuring that it is no larger than the shape you traced.5) Attach the speaker wires to the terminals on the back of the speaker. Use RED for the positive (+) wire and BLACK for the negative (-) wire.6) Position the speaker and tighten the six screws until snug.
CAUTION: DO NOT OVER-TIGHTEN SCREWS!7) Install grille. | <ol style="list-style-type: none">1) Déterminez l'emplacement. Assurez le dégagement adéquat des montants/solives.2) Tenez ou fixez le gabarit sur l'emplacement déterminé.3) Tracez le pourtour du gabarit.4) Taillez l'embrasure. Assurez-vous qu'elle n'est pas plus grande que le tracé.5) Connectez les câbles de h.p. aux bornes situées à l'arrière du haut-parleur. ROUGE = fil positif (+) / NOIR = fil négatif (-).6) Installez le haut-parleur et serrez fermement les six vis.
ATTENTION: NE SERREZ PAS TROP LES VIS!7) Installez la grille. |
|--|---|

HBP2219